

ONTARIO

AERODROME / FACILITY DIRECTORY

KITCHENER / WATERLOO ON (Cont'd)

CYKF

RWY DATA	Rwy 14(138°)/32(318°) 4103x148 ASPH Rwy 08(075°)/26(255°) 7003x148 ASPH Rwy 26 down 0.44% RESA: 08 197'; 26 295'
RWY CERT	Rwy 14/32 AGN IIIA Rwy 08 RVR 1200(1/4sm)/Rwy 26 RVR 1200(1/4sm) AGN IIIB
TWY CERT	Twy B AGN IIIA
APRON	Apron I max wingspan 50'. Apron II max wingspan 55'. Turbine acft PPR. Apron IIIA tml apron for air carriers only. Max wingspan 118', larger acft PPR. Apron IIIB GA freight max wingspan 118', larger acft PPR. Apron IV max wingspan 118'. Apron V max wingspan 79'. Apron VII max wingspan 170'.
RCR	Aprt Ops 519-648-3370 CRFI/RSC avbl H24. PCN
LIGHTING	08-AO(TE HI) P2, 14-(TE HI) P1, 26-AN(TE HI) P2, 32-(TE HI) P1 ARCAL-126.0 type K when twr clsd. PAPI Rwy 14, 32 and 26 not avbl on ARCAL, on continuously: low ints at SS minus 30 min to SR minus 30 min, high ints at SR minus 30 min to SS minus 30 min.
COMM	ATIS 125.1 12-04Z± GND Waterloo 121.8 12-04Z± TWR Waterloo 126.0 118.55 (V) 12-04Z± (emerg only 519-648-3055) MF tfc 126.0 04-12Z± 5NM 4000 ASL (CAR 602.98) ARR Toronto Tml 128.275 DEP Toronto Tml 128.275 PAL Toronto Ctr 128.275 AWOS 125.1 04-12Z±
NAV	DME WATERLOO YWT 115.0 Ch 97 N43 27 31 W80 22 46 (1047') ILS IKF 110.7 (Rwy 26)
PRO	Pursuant to CAR 602.105, the following procedures are in effect. Noise Abatement pro in effect for all acft. See CAP or VTPC. Pilots flying an inst apch pro to Rwy 26 take note: The pro turn overflies Guelph Aprt (circuit hgt 2100 ASL). Pilots flying an inst apch pro to Rwy 26 can anticipate delays and/or restrictions when Rwy 05 & 06R are in use at Toronto/Lester B. Pearson. IFR tng flts are to ctc National Traffic Management Unit (FLOW CTL) 800-268-4831 2 hrs prior to ETD or possible delays. VFR tfc outside CZ watch for apch acft oprg in vic of extended Rwy 26 centreline. VFR dep avoid noise sensitive areas at an operationally safe alt. Pursuant to CAR 602.105, the following procedures are in effect. Rgt hand circuits Rwy 32 (CAR 602.96). No VFR or IFR tng on Rwy 08 btwn 02-12Z± REDUCED VISIBILITY OPERATING PROCEDURES (RVOP): One acft permitted on manoeuvring area at a time dur RVOP. RVOP avbl 12-04Z± only. For VFR ARR/DEP rtes see Kitchener/Waterloo VTPC.
CAUTION	Winch-launched hang gliders, cable to 2000 AGL N43 33 18 W080 31 31 near St. Jacobs aprx 8.5NM NW of A/D.