
QUEBEC

AERODROME/FACILITY DIRECTORY

QUÉBEC / JEAN LESAGE INTL QC

CYQB



OUEBEC

AERODROME/FACILITY DIRECTORY

CYQB CUST AOE 888-226-7277 H24 Dec 1-Apr 30, 13-05Z‡ May 1-Nov 30 FLT PLN (bil) FIC Québec 866-GOMÉTÉO or 866-WXBRIEF (Toll free within Canada) or 866-541-4105 (Toll free within Canada & USA) or 418-871-8678 ACC Montreal 514-633-3211 or 800-633-1353, all Fit Pins, IFR tng PPR WX METAR H24. TAF H24, issue times: 00, 06, 12, 18Z. SERVICES Call out cho may be levied for one or more sycs FUEL 100LL, JA-1 OIL All 1.2.4.5.6 S ARFF **DESIGNATED CAT 7** SUP FL D & A-ice JASU Elect Start 10/15 **PVT ADV** Avjet 123.0/122.95 10-02Z⁺ 418-871-1958; TSAS 122.9 10-03Z⁺ Mon-Fri, 1000-0230Z[±] Sat-Sun 418-877-6708, 888-592-3835; Services Aériens du Québec ctc dispatch 129.625 prior to arr and dep 20 min PPR; Air Liaison/Skyjet 129.17 11-15Z⁺ 2030-2300Z⁺ Mon-Fri 418-872-0999; AFS Exécutif 122.475 10-02Z⁺ 418-877-4419; Les Ailes Québécoises Inc. 129.85; Lux FBO 122.825 10-03Z± 418-649-8999 MIL CON Avjet Distributions Inc. 418-871-1958 RWY DATA Rwy 06(061°)/24(241°) 9000x150 ASPH Rwy 24 up 0.3% Rwy 11(114°)/29(294°) 5700x150 ASPH RWY CERT Rwy 06 RVR 1200(1/4sm)/Rwy 24 RVR 1200(1/4sm) AGN V Rwy 11/29 AGN IIB TWY CERT Twy A AGN IV Twy C AGN IIIB APRON Apron I: Btwn stand 33-37 rstd to taxiing acft with wingspan less than 118'. Apron II and III rstd to taxiing acft with wingspan less than 118'. Acft with wingspan 118' or greater must be towed. No parking on apron III. Parking proh without perms 418-640-0707. RCR Opr 13-21Z‡ Mon-Fri May 1-Oct 31, H24 Nov 1-Apr 30. CRFI, PCN LIGHTING 06-AN(TE HI) P3, 24-AN(TE HI) P3, 11-AO(TE ME) P2 offset 12° to the S, 29-AO(TE ME) P2 COMM (bil) RCO Québec rdo 123.275 (FISE) 126.7 (bcst) ATIS (English) 134.6; (French) 128.3 GND Québec 121.9 250.0 Québec 118.65 236.6 (E) (emerg only 418-871-7691) TWR TML Québec 124.0 VFR 127.85 IFR 322.8 PAL Montréal Ctr 135.025 270.9 NAV DME YQO 113.2 Ch 79 N46 47 49 W71 23 34 (312') IQB 109.5 (Rwy 06) RVR ILS

QUÉBEC / JEAN LESAGE INTL QC (Cont'd)

OUEBEC

QUÉBEC / JEAN LESAGE INTL QC (Cont'd) CYOB PRO Certain acft code AGN IIIB, AGN IV and higher, are not auth to perform 180° turns on any rwy without perms 418-640-0707. Tng Flts dep aprt to CYA616T as per VTPC to cross St-Augustin at 2000 ASL & maintain until St-Gilles checkpoint. Arr ctc tml leaving CYA616T & continue as per VTPC. St-Lambert (town) checkpoint enter CZ 2500 ASL. Pilots should refer to Canadian Airport Charts (CAC) to obtain details on established hot spots, prior to operating on maneuvering areas. CAC are available for free on the NAV CANADA website. Paragliding: Paragliding activities in the region of Mont-Ste-Anne refer to QUÉBEC VTPC - GLIDER OPERATIONS. Circuits: Rgt hand circuit Rwy 24 (CAR 602.96). REDUCED VISIBILITY PROCEDURES (RVR less than 2600 to 1200 ft) Reduced Visibility operations - 24 hours Reduced Visibility Operations on Rwy 06-24: these are operations when reported visibility is less than RVR 2600 feet or 1/2 statute mile and greater than or equal to RVR 1200 feet or 1/4 statute mile, per advisory circular CI 302-001. Low visibility operations (LVOP) (below RVR 1200') are not permitted. **DEPARTURES & ARRIVALS** "Follow-me" car A Follow-me car will be available at all times, under any circumstances, upon a pilot's request. This service is available for one aircraft at a time based on first come, first served principles: some exceptions may apply. During RVOP conditions, run-ups and towing will not be authorized on the maneuvering areas. Furthermore, vehicle access to the maneuver area during reduced visibility operations is restricted to essential operational functions only. Operation Terms 20 minutes prior to a flight's departure or arrival, the pilot shall contact Nav Canada's ground controller to request a "Follow-me" car escort for taxiing on the manoeuvring area. The pilot shall provide the following information: Exact position on the airfield (gate or FBO); Type of aircraft and airline; Flight departure time (if available); Runway used for take-off: The "Follow-me" car will position itself 30m in front of the aircraft. Hazard lights will be activated when ready for taxiing and for the duration of the escort procedure. Upon receiving authorization to proceed, the "Follow-me" car will follow the guide lines at no more than 30kph (16 knots) up to the desired destination. Night Only: When reported visibility is less than RVR 1800 or 3/8 SM, a "Follow-me" car is mandatory per advisory circular AC 302-004. DEPARTURE: Dep within CZ outside of QUÉBEC / JEAN LESAGE INTL aprt bdry, ctc Québec qnd prior tkof. If unable, call Québec twr at 418-871-7814. RUNWAY LEVEL OF SERVICE Rwy 06 RVR 1200 Rwy 24 (1/4 sm) Preferential rwy: Anticipate Rwy 06/24 in crosswinds up to 25 kt at 090° instead of Rwy 11. NOISE

Unless otherwise instructed by ATC, all helicopters climbing over populated areas to have best rate of climb and avoid low flying over populated areas.

QUEBEC

AERODROME/FACILITY DIRECTORY

QUÉBEC / JEAN LESAGE INTL QC (Cont'd)

OIGL	

PRO (Cont'd)	ATC:
· · · · ·	IFR Clnc Acknowledgement:
	IFR clnc read back with Québec Twr gnd shall include acft call sign, assigned SID
	name and transponder code.
HELI	All heli must ctc Ground Ctl. Avoid overflying north shore of Lac St-Augustin. ROUTES: (See Québec Heli VTPC)
	-Église: For arr & dep via Église, proceed to a point 1.5NM E, heading 264°/084°.
	-Montagne: For arr & dep via Montagne, proceed to a point 1NM NW, heading 150°/330° not above 750 ASL.
	-Chemin de fer: For dep via Chemin de fer, fly heading 104° to a point 1.7NM SE, then
	follow the railway to Robert-Bourassa highway.
	For arr via Chemin de fer, follow the railway from Robert-Bourassa highway to a point 1.7NM SE and then fly heading 284°.
	-Ste-Foy: Starting at highway Henry IV, follow highway Charest heading west until the intercepting Rwy 29 final at 1000 ft ASL or higher. Then proceed to the airport following the Rwy 29 final approach. Avoid flying over Rwy 29.
	Capitale Hélicoptère arr/dep proc: refer to QUÉBEC / CAPITALE HÉLICOPTÈRE QC (Heli) PRO.
	Release and banner towing prohibited PPR Opr 418-640-0707
CAUTION	Twin antennas aprx 2035' N of thId of Rwy 24, 140 AGL, 336 ASL, only one antenna painted & lighted.