

ALBERTA

AERODROME/FACILITY DIRECTORY


CALGARY / YYC CALGARY INTL AB

CYYC

ELEV 3606

CZ "C" 7NM TO 6600
6100
SHAPE IRREGULAR

Hot spots see PRO section



ALBERTA

AERODROME/FACILITY DIRECTORY

CALGARY / YYC CALGARY INTL AB (Cont'd)

CYYC

REF	N51 06 50 W114 01 13 15°E (2013) UTC-7(6) Elev 3606' A1904 A5005 LO2 HI3 T1 CAP OC
OPR	The Calgary Airport Authority 403-735-1300 H24 Cert Ldg fees
PF	A-1,2,3,4,5,6
CUST	AOE 888-226-7277
FLT PLN	<p>Pilots are to open/close VFR Flt Pln with Edmonton FIC via phone or Edmonton rdo 123.375 when practicable.</p> <p>FIC Edmonton 866-WXBRIEF (Toll free within Canada) or 866-541-4102 (Toll free within Canada & USA)</p> <p>ACC Edmonton IFR 888-358-7526</p> <p>WX METAR H24.</p> <p>DUAT TAF H24, issue times: 00, 03, 06, 09, 12, 15, 18, 21Z.</p> <p>DUAT Esso Avitat; Shell Aerocentre</p>
SERVICES	<p>FUEL 100LL, JA-1 (FSII avbl), HPR</p> <p>OIL All</p> <p>S 1,2,3,4,5,6</p> <p>ARFF DESIGNATED CAT 9</p> <p>SUP FL LHOX D & A-ice</p> <p>JASU CE16, Elect start 15/25</p> <p>PVT ADV Esso Avitat/Skyservice 128.85 403-291-4426; Shell AeroCentre/Sunwest Aviation 136.80 403-275-8121; Skyplan dispatch 122.95 403-275-2520; North Cariboo Air 131.25 403-717-1800 866-266-8690; Executive Flight Centre 122.0 403-295-7741 Fax 403-295-7784; Million Air FBO (AvFuel) 128.9 403-718-0447; Landmark Aviation/Signature Flight Support 122.85 403-295-4100</p> <p>MIL CON Skyservice Calgary FBO 403-592-3741</p>
RWY DATA	<p>Rwy 17L(165°)/35R(345°) 14,000x200 CONC</p> <p>Rwy 17R(165°)/35L(345°) 12,675x200 ASPH</p> <p>Rwy 11(105°)/29(285°) 8000x200 ASPH</p>
RWY CERT	<p>Rwy 17L RVR 600/Rwy 35R RVR 600 AGN VI</p> <p>Rwy 17R RVR 1200(1/4sm)/Rwy 35L RVR 1200(1/4sm) AGN VI</p> <p>Rwy 11 RVR 1200(1/4sm)/Rwy 29 RVR 1200(1/4sm) AGN VI</p>
TWY CERT	<p>Twy: AB, GB, JT, LB, P, WB AGN IIIB</p> <p>Twy L: AGN IIIB fr Twy LB to Twy A & AGN IV fr Twy A to Twy N</p> <p>Twy: M, N, W, YB AGN IV</p> <p>Twy: A, A1, A3, C, C1, C2, C3, C4, C6, F, F1, G, GD, H, HB, HD, J, J2, K, U, Y, YD, YE AGN V</p>
TWY	<p>Twy AB, GB, JT, P, WB, YD & YE rstd to acft with wingspan of 118' or less.</p> <p>Twy GB & GD rstd to one-way westbound.</p> <p>Twy GB, GD & P uncontrolled.</p> <p>Twy L: W of Twy A rstd to acft with wingspan of 118' or less.</p> <p>Twy M, N & W rstd to acft with wingspan of 170' or less.</p> <p>WIDE BODY AIRCRAFT:</p> <p>Twy C: right turn on YB rstd to acft with wingspan of 118' or less.</p> <p>Twy F: left turn on F1 rstd to acft with wingspan of 79' or less. Left turn on G rstd to acft with wingspan of 118' or less.</p> <p>Twy F1: right turn on F rstd to acft with wingspan of 79' or less.</p> <p>Twy G: right turn on F rstd to acft with wingspan of 118' or less.</p> <p>Twy J (eastbound): right turn on J2 rstd to acft with wingspan of 79' or less.</p> <p>Twy J2: left turn on J rstd to acft with wingspan of 79' or less.</p> <p>Twy Y: right turn on YB rstd to acft with wingspan of 118' or less.</p> <p>Twy YB: left turn on C rstd to acft with wingspan of 118' or less. Left turn on Y rstd to acft with wingspan of 118' or less.</p>
APRON	Aprons I, VII, IX, X & West De-Ice: PPR Airport Ops is required.
RCR	Opr CRFI, PCN

ALBERTA

AERODROME/FACILITY DIRECTORY

CALGARY / YYC CALGARY INTL AB (Cont'd)

CYYC

LIGHTING	11-AO(TE ME) P3, 29-AN(TE ME) P3, 17L-AL(TE HI A TDZL) P3, 35R-AL(TE HI A TDZL) P3, 17R-AL(TE HI CL TDZL) P3, 35L-AL(TE HI CL TDZL) P3
COMM	
RCO	Edmonton rdo 123.375 (FISE) 126.7 (bcst)
ATIS	128.225
CLNC DEL	120.825 all dep acft ctc CLNC DEL
APRON	APRON I: Apron Advisory 121.3 12-07Z‡ O/T bcst intentions
GND	121.9 (West) 125.35 (East) 275.8
TWR	118.4 (West) 118.7 (East) 236.6 (E) (emerg only 403-216-7116)
ARR	126.525 (West) 125.9 (East) 123.85 127.15 294.9
DEP	119.8 (East) 124.52 (West) 255.1
VFR ADV	119.4
PAL	Edmonton Ctr 124.525 127.775 243.5
NAV	
VOR/DME	YYC 116.7 Ch 114 N51 06 55 W113 52 55 (3573')
DME	IYC 111.5 Ch 52 N51 05 57 W114 01 23 (3559') IGY 110.55 Ch 42(Y) N51 07 28 W114 02 00 (3570') ILG 109.15 Ch 28(Y) N51 08 44 W113 59 19 (3628') IRF 110.75 Ch 44(Y) N51 06 46 W113 59 19 (3603')
ILS	IYC 111.5 (Rwy 35L) RVR IEM 109.3 (Rwy 17R) RVR ILG 109.15 (Rwy 17L) RVR IRF 110.75 (Rwy 35R) RVR IAQ 110.9 (Rwy 29) RVR IGY 110.55 (Rwy 11) RVR
PRO	<p>Acft less than 3000 kg not auth for arr or dep 23-05Z‡ exc heli. Pilots should refer to Canadian Airport Charts (CAC) to obtain details on established hot spots, prior to operating on maneuvering areas. CAC are available for free on the NAV CANADA website.</p> <p>AIRSPACE: see VTPC for VFR routes & pro. Transponder rqrd in class "C" & "D" airspace & CZ. Pilots to close VFR flt plans with Edmonton FIC (phone) when practicable or request closure fr ATC. Pilots of acft not filing a VFR or IFR flt pln within or into Calgary Class "C" Airspace, are to ctc ATC 888-882-2254 for transponder code prior to flt. PPR for Balloon flt in Calgary CZ. Balloon flt is rqrd to remain min 4NM fr any rwy. Ctc Edmonton ACC 888-882-2254.</p> <p>VFR city tours in Class C airspace over the Calgary downtown area may be denied when Rwy 17L or 17R are act at CYYC.</p> <p>AIRPORT: High intensity rwy ops in effect.</p> <p>ATC: IFR Clearance Acknowledgement IFR clearance read back with Calgary Tower clearance delivery shall include the acft call sign, assigned SID name and transponder code.</p> <p>MULTILATERATION: Acft transponders must be kept on at all times when manoeuvring on the airport (turned on prior to brake release and on arrival, on until final engine shutdown).</p> <p>Pilots that do not have a transponder code issued by ATC must squawk 1000 when taxiing.</p> <p>PEAK HOURS: 23-05Z‡</p> <p>CIRCUITS: No circuits.</p> <p>TRAINING FLIGHTS: No ab initio tng. PVT pilot's license min rqrd for ops in CZ. Round-robin, test and tng flts proh during peak hrs. PPR for all round-robin, test or tng flts outside peak hrs: ctc ATC 888-882-2254. Helis exempt.</p> <p>LOW AND REDUCED OPERATING PROCEDURES (LVOP/RVOP): See CAP</p> <p>NOISE: Noise oprg restriction & noise abatement procedure in effect. See CAP</p> <p>MILITARY: Mil jet acft circuits & overhead break pro proh.</p>

ALBERTA

AERODROME/FACILITY DIRECTORY

CALGARY / YYC CALGARY INTL AB (Cont'd)

CYYC

PRO (Cont'd)	<p>AIRPORT RESERVATION OFFICE (ARO): Airport Reservation Office (ARO) pro for all general & business aviation acft oprg IFR & VFR flts. Opr must file a dep & arr reservation through the Online Coordination System (OCS): www.online-coordination.com. More info avbl at Airport Reservation Office (ARO) (yyc.com): email aro@yyc.com or call 403-735-1300.</p>
	<p>DE-ICING PROCEDURES:</p> <ol style="list-style-type: none"> 1. Contact CALGARY DE-ICE on 129.5 30 min prior to push-back with acft type and estimated push-back time. 2. Contact CALGARY DE-ICE on 129.5 5 min prior to push-back to confirm treatment type and DE-ICE pad assignment. 3. Follow normal push-back procedures and advise Apron Advisory EAST or WEST DE-ICE pad has been assigned. 4. East Pad - Enter from Twy J at Twy JQ. When instructed by GROUND CONTROL, contact PAD CONTROL on 129.125 prior to entering pad. 5. West Pad - Enter from Twy J at Twy JV. When instructed by GROUND CONTROL, contact PAD CONTROL on 122.35 prior to entering pad. 6. Follow PAD CONTROL instructions, signboards and guidance lines to the assigned staging position or de-icing bay and confirm "BRAKES SET" when in position with nosewheel on stop bar.
	<p>AUTOMATIC MODE (Active signboard guidance): As the acft enters the de-icing bay, proximity capturing devices will recognize the acft. The signboards will actively guide the acft to the stop bar position and the signboard will advise SET PARK BRAKE.</p>
	<p>MANUAL MODE (Automatic mode not operational): Follow the instructions from PAD CONTROL and stop on the designated stop bar. Nosewheel should be placed as close to the stop bar marking as possible.</p>
	<p>CAUTION: The wingtip to tail clearance for acft taxiing in the EAST pad from JQ behind staged acft is only assured when the staged acft nosewheel is on the stopbar.</p>
	<ol style="list-style-type: none"> 7. If assigned a staging bay, monitor PAD CONTROL until further instructed. 8. When directed by PAD CONTROL, contact ICEMAN (East 123.35, West 122.725) and confirm "BRAKES SET, AIRCRAFT CONFIGURED FOR DE-ICE." 9. When de-ice is complete, do not move acft. When directed by ICEMAN, contact PAD CONTROL on assigned frequency. 10. Advise PAD CONTROL when ready to taxi. PAD CONTROL will assign appropriate GROUND CONTROL frequency to obtain taxi clearance. 11. Queuing is not permitted on Twy J, staging positions are provided on both EAST and WEST pads, reference DE-ICE Facility diagram.
	<p>See CAP for additional directions & restrictions.</p>
	<p>CAUTION: During the de-icing process, thrust setting must not exceed gnd idle and/or propellers must remain feathered at all times.</p>
	<p>Engine run-ups will only be approved by PAD CONTROL or ICEMAN when ops permit and when it is safe to do so. Engine fan blade ice shedding run-ups are proh on the de-ice pads.</p>
CAUTION	Coyotes at large on apt. Extv waterfowl activity vic A/D year round.