

NOISE ABATEMENT PROCEDURES

General

Pursuant to CAR 602.105, the following procedures apply at Hamilton Airport.

Departure

Rwy	NADP
All rwys	1 or 2

Departures not permitted on rwy 06, between 2300 and 0700 local time unless authorized by Airport Duty Manager.

Rwy 12:

Climb on rwy hdg to **3000'** ASL before proceeding on course.

Rwy 30:

Climb on rwy hdg to **1300'** ASL. Turn left hdg **260°**. No right turn below **4000'** ASL.

Rwys 06, 24:

Climb on rwy hdg to **3000'** ASL before proceeding on course.

Arrival

Arrivals not permitted on, and approaches not permitted to, rwy 24, between 2300 and 0700 local time unless authorized by the Airport Duty Manager.

Visual Arrivals:

- a. Aircraft 26,000 kg and over (max cert gross take-off weight) maintain **3000'** ASL over the Minimum Altitude Area (depicted on the VTTC) and North of rwy 12/30 except on final apch to rwy 24, after takeoff from rwy 06, or circling to land after conducting an instrument approach procedure.
- b. Remain on or above ILS glide slope or assumed 3° glide path.

Reverse Thrust

Consistent with safety of operations, pilots should minimize reverse thrust when using rwys 12 and 30.

Training Flights

Training flights not permitted between 2300 and 0700 local time unless authorized by the Airport Duty Manager.

Inquiries

Contact the Airport Duty Manager at 905-667-8781 between the hours of 0900 and 1700 local time, or after hours to request authorization for exemption to the noise abatement procedures.

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved