

**Departure Route Description**

- Rwy 06:** 1. Requires a minimum climb gradient of **240 ft/NM** to **2300**.  
2. Climb hdg **061°** or as assigned by ATC for radar vectors.  
Maintain **4000** or as assigned.
- Rwy 11:** 1. Climb hdg **114°** or as assigned by ATC for radar vectors.  
2. Unless otherwise assigned by ATC:  
Non-jet aircraft maintain **3000**.  
Jet aircraft maintain **4000**.
- Rwy 24:** 1. Climb hdg **241°** or as assigned by ATC for radar vectors.  
2. Unless otherwise assigned by ATC:  
Non-jet aircraft maintain **3000**.  
Jet aircraft maintain **4000**.

DEPARTURE CLIMB RATE V/V (FPM)

| GROUND SPEED | 90  | 120 | 140 | 160 | 180 | 200 | 250  | 300  |
|--------------|-----|-----|-----|-----|-----|-----|------|------|
| 240 FT/NM    | 360 | 480 | 560 | 640 | 720 | 800 | 1000 | 1200 |

**Note:** Refer to Noise Abatement Procedures for additional requirements.

**Communication Failure**

1. Select transponder code 7600.
2. Climb to flight planned altitude 3 minutes after take-off, and;
3. Proceed on course 3 minutes after selecting 7600.