

DEPARTURE PROCEDURE

Departure Procedure

- Rwy 06 – ½:** Requires a minimum climb gradient of **290** ft/NM to **5300**. Climb between hdg **035°** CW to **241°** to remain clear of CYR603 and CYR612.
or
SPEC VIS – Climb in visual conditions to cross the aprt at or above **2500** then climb between hdg **064°** CW to **264°** to remain clear of CYR603 and CYR612 BPOC.
- Rwy 11 – ½:** Requires a minimum climb gradient of **320** ft/NM to **5200**. Climb between hdg **035°** CW to **291°** to remain clear of CYR603 and CYR612.
Note: Trees to 300 ASL abeam departure end of rwy, 450' LEFT of rwy centreline and 0.1 NM past departure end of rwy, 650' RIGHT of centreline.
or
SPEC VIS – Climb in visual conditions to cross the aprt at or above **2500** then climb between hdg **064°** CW to **264°** to remain clear of CYR603 and CYR612 BPOC.
- Rwy 24 – ½:** Requires a minimum climb gradient of **320** ft/NM to **5300**. Climb between hdg **280°** CCW to **061°** to remain clear of CYR603 and CYR612.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2500** then climb between hdg **064°** CW to **264°** to remain clear of CYR603 and CYR612 BPOC.
- Rwy 29 – ½:** Requires a minimum climb gradient of **340** ft/NM to **5300**. Climb between hdg **273°** CCW to **114°** to remain clear of CYR603 and CYR612.
Note: Terrain to 242 ASL abeam departure end of rwy, 400' LEFT of rwy centreline.
or
SPEC VIS – Climb in visual conditions to cross the aprt at or above **2500**. Then climb between hdg **064°** CW to **264°** to remain clear of CYR603 and CYR612 BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
290 FT/NM	440	580	680	780	870	970	1210	1450
320 FT/NM	480	640	750	860	960	1070	1340	1600
340 FT/NM	510	680	800	910	1020	1140	1420	1700

DEPARTURE PROCEDURE

CYQB

EFF 31 OCT 24