

Departure Route Description

**Rwy 29:** Requires a minimum climb gradient of **400** ft/NM to **1900**. Do not exceed 220 kt until XUBUN. Climb track **294°** to TILAC, then climbing LEFT turn direct to XUBUN. Climb and maintain **7000**.

**Note:** Trees to 305 ASL aprx 150' past departure end of rwy, 500' LEFT and RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

| GROUND SPEED | 90  | 120 | 140 | 160  | 180  | 200  | 250  | 300  |
|--------------|-----|-----|-----|------|------|------|------|------|
| 400 FT/NM    | 600 | 800 | 940 | 1070 | 1200 | 1340 | 1670 | 2000 |

**OLAVO TRANSITION:** Passing XUBUN, climbing RIGHT turn, track **330°** to OLAVO. (TILAC2.OLAVO)

**IKMIK TRANSITION:** Passing XUBUN, climbing LEFT turn, track **198°** to IKMIK. (TILAC2.IKMIK)

**FLEUR TRANSITION:** Passing XUBUN, climbing LEFT turn, track **165°** to UKPOB, (TILAC2.FLEUR) then track **123°** to VIXUV, then track **062°** to FLEUR.

**Note:** Refer to Noise Abatement Procedures for additional requirements.

Communication Failure

On recognition of failure 10 minutes or less after take-off and in IFR weather conditions proceed as follows:

- 1. Select transponder code 7600;
- 2. Upon reaching end of transition, proceed on course and climb to flight planned altitude.

**Note:** If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.