

ENGINE FAN BLADE ICE SHEDDING PROCEDURES

CYUL

The undertaking of aircraft engine run-up for engine fan-blade ice-shedding must be conducted on taxiway areas outlined in ENGINE FAN-BLADE ICE-SHEDDING PROCEDURES. Strict adherence to the center line is mandatory during engine fan-blade ice-shedding. The crew must make first contact on the clearance frequency (125.6 MHz), to provide the following information:

- De-Icing requirements
- Ice-shedding requirements before takeoff
- Runway run-up requirements on the runway before takeoff

In addition, the following elements needs be considered:

- The crew will communicate on the Ground frequency (121.9 MHz or 121.0 MHz) to report any changes that occur following initial contact. NAV CANADA must be informed if the ice-shedding procedure has been completed on taxiway Juliette.
- If the taxiway surface conditions are not suitable for the crew, communication must be made to ATC to arrange another location.

Departing Rwy 24R Ice-Shed Area (IS) see chart.

- IS1 Taxiway B short of holding bay 24R. Available for aircraft AGN V & smaller.
- IS2 Taxiway B short of taxiway B5. Available for aircraft AGN V & smaller.
- IS3 Taxiway B short of taxiway B3. Available for aircraft AGN IIIB & smaller.

Departing Rwy 06L Ice-Shed Area (IS) see chart.

- IS4 Taxiway B short of taxiway B4. Available for aircraft AGN V & smaller.
- IS5 Taxiway B short of taxiway B6. Available for aircraft AGN V & smaller.

Departing Rwy 24L Ice-Shed Area (IS) see chart.

- IS6 Taxiway A short of taxiway A5. Available for aircraft AGN V & smaller.
- IS7 Taxiway A short of taxiway A3. Available for aircraft AGN IIIB & smaller.
- IS8 Taxiway A short of taxiway A1. Available for aircraft AGN V & smaller.
- IS9 Taxiway A short of taxiway A2. Available for aircraft AGN IIIB & smaller.

Departing Rwy 06R Ice-Shed Area (IS) see chart.

- IS10 Taxiway A short of taxiway C. Available for aircraft AGN V & smaller.
- IS11 Taxiway A short of taxiway A4. Available for aircraft AGN V & smaller.

Additional locations depending on operational needs.

- IS12 Facing East on taxiway C short of taxiway D. Available for aircraft AGN V & smaller.
- IS13 Facing West on taxiway C short of taxiway E. Available for aircraft AGN V & smaller.
- IS14 Facing East on taxiway J short of taxiway U. Available for the following aircraft belonging to AGN IIIB: all Embraer, CRJ and Airbus. No B737 group aircraft is authorized to perform the ice-shedding procedure on taxiway J.