

Departure Procedure

- Rwy 03 – ½:

Requires a minimum climb gradient of **310** ft/NM to **2600**. Climb between hdg **029°** CW to **274°** to remain clear of CYR229, CYR230 and CYR231.

Note:

Trees to 2375 ASL 0.2 NM past departure end of rwy, 170' left of rwy centreline.

or

SPEC VIS – Climb in visual conditions to cross the aprt at or above **3000**. Then climb between hdg **029°** CW to **274°** to remain clear of CYR229, CYR230 and CYR231 BPOC.
- Rwy 09 – ½:

Requires a minimum climb gradient of **310** ft/NM to **2600**. Climb between hdg **029°** CW to **274°** to remain clear of CYR229, CYR230 and CYR231.

or

SPEC VIS – Climb in visual conditions to cross the aprt at or above **3000**. Then climb between hdg **029°** CW to **274°** to remain clear of CYR229, CYR230 and CYR231 BPOC.
- Rwy 21 – ½:

Climb between hdg **029°** CW to **274°** to remain clear of CYR229, CYR230 and CYR231.

Note:

Tanks to 2370 ASL 0.2 NM past departure end of rwy, 240' left of rwy centreline.
- Rwy 27 – ½:

Requires a minimum climb gradient of **250** ft/NM to **6800**. Climb between hdg **280°** CCW to **029°** to remain clear of CYR229 and CYR230.

or

SPEC VIS – Climb in visual conditions to cross the aprt at or above **3000**. Then climb between hdg **274°** CCW to **029°** to remain clear of CYR229, CYR230 and CYR231 BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250
310 FT/NM	470	620	730	830	930	1040	1300	1550