

NOISE ABATEMENT PROCEDURES

Application

These procedures apply to JET AIRCRAFT unless noted otherwise.

Preferential Runways (All Aircraft)

ATC will designate runways to divert as many take-offs as possible, consistent with safety of operations, from flight over residential areas adjacent to the airport. Use of other than designated runways should only be requested to meet operational necessity.

Taking into consideration the following conditions and except as authorized by ATC, all aircraft will use the following preferential runways:

All Aircraft		
Operation	Local Time	Preferential Runway
ARRIVALS		
	Monday-Friday 06:00-07:00	35R
	Monday-Friday 07:00-23:00 Saturday-Sunday 09:00-23:00	35L, 35R
	Monday-Friday 23:00-06:00 Saturday-Sunday 23:00-09:00	17R, 17L, 29
DEPARTURES		
	All hours	35L, 35R
ICAO Annex 16 Chapter 2 (FAA Stage 2) and non-noise certified aircraft departures – ALL HOURS		35L, 35R

- 1. Physical condition of surface.
- 2. Effective crosswind component not to exceed 15 knots for arrivals, 20 knots for departures.
- 3. Effective tailwind component not to exceed 5 knots.
- 4. Other Safety considerations declared by the Captain of the aircraft.

Departure Procedures

Rwy	NADP
All rwys	1 or 2

SID cancellation does not terminate Noise Abatement Procedure. ICAO Annex 16 Chapter 2 (FAA Stage 2) and non-noise certified military aircraft will be assigned rwy 35L for departures when rwys 29 and 35L are in use.

Runway	Noise Abatement Procedures
11, 29	SID routing shall be followed to 6500' .
17L	No left turns beyond hdg 155 or no right turns beyond hdg 185 below 6500' .
17R	No right turns below 6500' . No left turns beyond hdg 135 below 6500' .