

Departure Route Description

**Rwy 05 - ½:** Do not exceed 210 kt until RABIK. Requires a minimum climb gradient of **420 ft/NM to 2600**. Climb hdg **053° to 1400**. Then climbing **RIGHT** turn direct RABIK to **5000** or as assigned. As required shuttle climb and hold at RABIK as published. Expect further clearance 10 minutes after take-off.

**Rwy 23 - ½:** Do not exceed 210 kt until RABIK. Requires a minimum climb gradient of **370 ft/NM to 2600**. Climb hdg **233° to 1000**. Then climbing **LEFT** turn direct RABIK to **5000** or as assigned. As required shuttle climb and hold at RABIK as published. Expect further clearance 10 minutes after take-off.

**Note:** Trees to 378 ASL aprx 0.1 NM from departure end of rwy, 600' **RIGHT** of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

| GROUND SPEED | 90  | 120 | 140 | 160  | 180  | 200  | 250  | 300  |
|--------------|-----|-----|-----|------|------|------|------|------|
| 370 FT/NM    | 560 | 740 | 870 | 990  | 1110 | 1240 | 1550 | 1850 |
| 420 FT/NM    | 630 | 840 | 980 | 1120 | 1260 | 1400 | 1750 | 2100 |

Communication Failure

1. Select transponder code 7600;
2. Proceed for the published hold at the last assigned altitude;
3. 10 minutes after entering the hold, you are cleared for an approach at CZBM or to continue enroute.