

CYDF

						RADIO – 122.2 239.6				CTR Gander – 134.6			
DECL DIST		07	25							MF			
TORA		8005	8005										
TODA		8989	8989										
ASDA		8005	8005										
LDA		8005	8005										

57 24.5

57 24

57 23.5

57 23

49 13

49 12.5

49 12

AN

181

2024

AN

↑

AN

181

2024

↑

ANNUAL RATE
OF CHANGE 12° E

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
290 FT/NM	440	580	680	780	870	970	1210	1450

Touchdown pads

A

B

8005 x 150

CYDF
N49 12.55
W57 23.66

* DEPARTURE PROCEDURE

Rwy 07

- ½ - NO LEFT turn below 1400.

Note: Trees to 138 ASL aprx 0.1 NM past departure end of rwy, 550' LEFT and RIGHT of rwy centreline.

Rwy 25

- ½ - Requires a minimum climb gradient of 290 ft/NM to 1900. Climb rwy hdg to 1200 BPOC.

SPEC VIS - Climb in visual conditions to cross the aprt at or above 1300 BPOC

Note: Trees to 117 ASL aprx 0.1 NM past departure end of rwy, 600' LEFT and RIGHT of rwy centreline.

57 24.5

57 24

57 23.5

57 23

49 12

49 12.5

49 13

RUNWAY LEVEL OF SERVICE

RVO

LVO

Rwy 07, 25: (¼sm)

NOT AUTHORIZED

TAKE-OFF MINIMA

Rwys 07, 25: ★

SCALE IN FEET

1000

0

1000

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved