



DEPARTURE PROCEDURE

Departure Procedure

- Rwy 04 – ½:** Requires a minimum climb gradient of **270** ft/NM to **600**. Climb between hdg **131°** CCW to **228°** to remain clear of CYA528 or CYA534 when active.
Note: Building to 359 ASL aprx 160' past departure end of rwy, 500' LEFT of rwy centreline. Trees to 410 ASL aprx 0.2 NM past departure end rwy.
- Rwy 07 – ½:** Climb between hdg **131°** CCW to **228°** to remain clear of CYA528 or CYA534 when active.
Note: Road to 377 ASL abeam departure end of rwy, 300' LEFT and RIGHT of rwy centreline. Trees to 433 ASL aprx 400' past departure end rwy, 400' LEFT and RIGHT of rwy centreline.
- Rwy 14 – ½:** No LEFT turn below **1000**. Requires a minimum climb gradient of **430** ft/NM to **5100** when CYA528 or CYA534 active.
Note: Trees to 443 ASL aprx 0.3 NM past departure end of rwy, 400' LEFT and RIGHT of rwy centreline.
- Rwy 22 – ½:** Requires a minimum climb gradient of **420** ft/NM to **5200** when CYA528 or CYA534 active.
Note: Trees to 410 ASL within 0.2 NM of departure end of rwy.
- Rwy 25 – ½:** Climb between hdg **228°** CW to **131°** to remain clear of CYA528 or CYA534 when active.
Note: Trees to 423 ASL aprx 0.1 NM past departure end of rwy, 300' LEFT of rwy centreline.
- Rwy 32 – ½:** Climb between hdg **228°** CW to **131°** to remain clear of CYA528 or CYA534 when active.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
270 FT/NM	410	540	630	720	810	900	1130	1350
420 FT/NM	630	840	980	1120	1260	1400	1750	2100
430 FT/NM	650	860	1010	1150	1290	1440	1800	2150

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

