

Departure Route Description

- All **rwys**: Maintain **3000**. Expect clearance to flight planned altitude/flight level 10 minutes after departure.
- Rwy **07**: Climb hdg **070°** or as assigned by ATC. Expect radar vectors to cross MALTB at or above **4000** then proceed via depicted route.
- Rwy **12**: Climb hdg **123°** or as assigned by ATC. Expect radar vectors to cross MALTB at or above **4000** then proceed via depicted route.
- Rwy **25**: Climb hdg **250°** or as assigned by ATC. Expect radar vectors to cross MALTB at or above **4000** then proceed via depicted route.
- Rwy **30**: Requires a minimum climb gradient of **210 ft/NM** to **1300**. Climb hdg **303°** or as assigned by ATC. Expect radar vectors to cross MALTB at or above **4000** then proceed via depicted route.
- Note**: Turbojet acft at or above **10000**. Maintain 280 kt until advised by ATC.

DEPARTURE CLIMB RATE V/V (FPM)								
GROUND SPEED	90	120	140	160	180	200	250	300
210 FT/NM	320	420	490	560	630	700	880	1050

LNCON TRANSITION:

BROKK TRANSITION:

(MALTB1.LNCON)

(MALTB1.BROKK)

Communication Failure

- On recognition of failure 5 minutes or less after take-off and in IFR weather conditions proceed as follows:
1. Select transponder code 7600;

2. Climb to **3000** on assigned heading;

3. Proceed direct to MALTB then via depicted route;

4. Climb to flight planned altitude 10 minutes after departure.