

Departure Route Description

- All rwys:** Climb to and maintain **4000**.
- Rwy 13:** Climb hdg **135°** or as assigned for vectors to assigned route.
- Rwy 18:** Requires a minimum climb gradient of **300 ft/NM** to **1200**. Climb hdg **185°** to 1.7 DME (YWI). Then climbing **LEFT** turn hdg **172°** for vectors to assigned route.
- Rwy 31:** Climb hdg **315°** or as assigned for vectors to assigned route.
- Rwy 36:** Requires a minimum climb gradient of **290 ft/NM** to **4000**. Climb hdg **005°** or as assigned for vectors to assigned route.

DEPARTURE CLIMB RATE V/V (FPM)									
GROUND SPEED	90	120	140	160	180	200	250	300	
290 FT/NM	440	580	680	780	870	970	1210	1450	
300 FT/NM	450	600	700	800	900	1000	1250	1500	

Note: Refer to Noise Abatement Procedures for additional requirements.

Communication Failure

- On recognition of failure 10 minutes or less after take-off and in IFR weather conditions, proceed as follows:
1. Select transponder code 7600;
 2. Fly last assigned hdg or track until 15 DME (YWI), and then proceed directly on course;
 3. Maintain last assigned altitude until 10 minutes after take-off, then;
 4. Climb to flight planned altitude.
- Note:** If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.