

Night Restrictions 23:00 - 07:00 Local Time

1. Reverse thrust above idle not permitted unless required for the safety of the acft.
2. Powerback ops not permitted.
3. Intersection dep rwy 13 or 18 not permitted.

General Noise Abatement Considerations

1. Circling procedures to runways 31 and 36 are not permitted.
2. When simulating power loss after take-off or overshoot on runways 13 or 18, power may be reduced on one engine to simulate emergencies provided:
 - a. All engines are returned to take-off or overshoot power before the aircraft crosses the departure end of the runway, or
 - b. The departure end of the runway is crossed at 300' or more above the ground and "one engine out" rate of climb is **500'** per minute or greater and is maintained to **2000 ASL**.
3. PPR for flight training and maintenance engine run ups. Ctc 204-987-9798. (See ATS REQUIREMENTS for additional PPR).

ATS Requirements (IFR)**Arrival Requirements**

1. On apch, cross the FAF at **170 kt** or less.
2. On a visual apch, intercept final at or outside the final apch FAF for landing rwy unless otherwise authorized by ATC.

Training Flight / Photo Block Requirements

PPR for all block air work, photo flight or training flight operating in Winnipeg TCA. Ctc Winnipeg ACC 204-984-5979 FAX 204-983-2823.

NOTE: Refer to NOISE ABATEMENT PROCEDURES for additional requirements.