

**Departure Route Description
(Non-Jet acft only)**

All rwsy: Climb to and maintain **7000** for vectors to assigned route or depicted fix.

Rwy 11: Climb hdg **105°** or as assigned.

Rwy 17L & 17R: Climb hdg **165°** or as assigned.

Rwy 29: Requires a minimum climb gradient of **300** ft/NM to **6500**.
Climb hdg **285°** or as assigned.

Rwy 35L & 35R: Climb hdg **345°** or as assigned.

DEPARTURE CLIMB RATE V/V (FPM)								
GROUND SPEED	90	120	140	160	180	200	250	300
300 FT/NM	450	600	700	800	900	1000	1250	1500

Communication Failure

On recognition of failure 10 minutes or less after take-off and in IFR weather conditions proceed as follows:

- 1. Select transponder code 7600;
- 2. Upon reaching the last assigned altitude proceed directly on course;
- 3. Maintain last assigned altitude for 10 minutes* after take-off; then,
- 4. Climb to flight planned altitude.

* West and Southwest bound flights - Proceed to the first enroute intxn at last assigned or acknowledged altitude, then shuttle climb to MEA BPOC.

Note: If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.