



ILS RWY 17L

ATIS – 128.22	ARR – 126.52 (W) 125.9 (E) 123.85 127.15	TWR – 118.4 (W) 118.7 (E) 236.6	GND – 121.9 (W) 125.35 (E) 275.8	TDZL
SAFE ALT 100 NM 13,800	LOC ILG 109.15	APCH CRS 165°	GP ULBUD 4890	LDA 14000



	11	10	9.1	8	7	6	5	4	3	2	1.4	DIST FROM DME (ILG)
	7110	6790	6500	6150	5830	5510	5200	4880	4560	4240	4060	ALT (3.00° APCH PATH)
VIKTI 7110 6500												
	MISSED APPROACH Climb to 4100 hdg 165° . Then climbing LEFT turn to hdg 110° . Intercept OBD "YYC" R-133 to OXANI.											
Procedure turn NOT AUTHORIZED.												
5200												
4.1												
2.9												
4800												
3.8												
MDA												
0.2 DME (ILG)												
TCH 57'												
ELEV 3606 TDZE 3606												
			CATEGORY	A		B		C		D		
			ILS/DME	3806		(200)		1/2 RVR 26				
Knots	ft/min	Min:Sec	LOC/DME	4060		(454)		1 RVR 50				
70	370											
90	480											
110	580											
130	690											
150	800											

ILS RWY 17L

EFF 9 JUL 26

CYYC

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved